

Motorola LS355

One Way Numeric Pager



- *6 Individual Addresses (cap codes)*
- *16 Message Slots*
- *12-digit LCD Backlit Display with 4 Icons*
- *Message Preview*
- *Message Time Stamping*
- *Message Full Indication*
- *Selective Erase/Erase All*

The LS355 has enhanced features such as memory backup, a message full indicator, discrete vibration, and a large backlit display for superb readability.

Enhanced features make this pager small in size yet big on convenience.

LS355 One Way Numeric Pager

This easy-to-carry pager has a host of advanced features that help users stay in touch. There are 16 message slots, with 6 individual addresses. Messages are time stamped, and can be erased selectively or all at once. There's memory backup, a message full indicator, discrete vibration, and a large backlit display for superb readability.

Model Number

A03GRS5961AA - VHF

A04GRS5961AA - UHF

Advanced Features That Help Users

Stay In Touch

Superb Readability

This easy-to-carry pager has a host of advanced features that help users stay in touch. There are 16 message slots, with 6 individual addresses.

specifications

LS355 PAGER FEATURES

- 6 Individual Addresses (cap codes)
- 16 Message Slots
- 12-digit LCD Backlit Display with 4 Icons
- Message Preview
- Message Time Stamping
- Message Full Indication
- Selective Erase / Erase All
- Saves Messages When Off or Changing Battery
- Time and Date on Standby
- Full Function Self Test
- Unread Message Indication
- Out of Range Indication
- Low Battery Alert and Indication
- RS232 Programmable
- POCSAG Technology
- AGC Function

VHF FREQUENCY RANGE

Band A	143-152 MHz
Band B	153-162 MHz
Band C	163-174 MHz

UHF FREQUENCY RANGE

Band A	450-459 MHz
Band B	460-470 MHz

SPECIFICATIONS

Transmission Speed:	512 / 1200 / 2400 Baud Rate
Modulation:	FSK +/- 4.5KHz
Channel Bandwidth:	25 KHz
Intermediate Frequency:	21.4MHz / 455KHz
Sensitivity:	5uv/m (512BPS) / 7uv/m (1200BPS) 9uv/m (2400BPS)
Adjacent Channel Selectivity:	55dB @ +/-25KHz
Image Frequency Rejection:	50dB
Spurious Response Rejection:	50dB
Intermodulation Rejection:	50dB
Alert Response:	75 dB @ 30 cm
Ambient Working Temperature:	-5 degrees C to - 40 degrees C
Battery:	1.5 Volt "AA" Alkaline x 1
Dimension (L x W x H):	68 x 50 x 18mm

